

AMENDMENT OF SOLICITATION/MODIFICATION OF CONTRACT			1. CONTRACT ID CODE		PAGE 1 OF 1 PAGES		
2. AMENDMENT/MODIFICATION NO. 0002		3. EFFECTIVE DATE 8 JAN 98		4. REQUISITION/PURCHASE REQ. NO.		5. PROJECT NO. (If applicable)	
6. ISSUED BY Department of the Army Corps of Engineers Fort Worth District		CODE		7. ADMINISTERED BY (If other than Item 6)		CODE	
8. NAME AND ADDRESS OF CONTRACTOR (No., street, county, State and ZIP Code)				(✓)		9A. AMENDMENT OF SOLICITATION NO. DACA63-98-B-0002	
				X		9B. DATED (SEE ITEM 11) 5 DECEMBER 1997	
						10A. MODIFICATION OF CONTRACTS/ORDER NO.	
						10B. DATED (SEE ITEM 13)	
CODE				FACILITY CODE			

11. THIS ITEM ONLY APPLIES TO AMENDMENTS OF SOLICITATIONS

☒ The above numbered solicitation is amended as set forth in Item 14. The hour and date specified for receipt of Offers ☒ is extended, ☐ is not extended.

Offers must acknowledge receipt of this amendment prior to the hour and date specified in the solicitation or as amended, by one of the following methods:

(a) By completing Items 8 and 15, and returning 1 copies of the amendment; (b) By acknowledging receipt of this amendment on each copy of the offer submitted; or (c) By separate letter or telegram which includes a reference to the solicitation and amendment numbers. FAILURE OF YOUR ACKNOWLEDGMENT TO BE RECEIVED AT THE PLACE DESIGNATED FOR THE RECEIPT OF OFFERS PRIOR TO THE HOUR AND DATE SPECIFIED MAY RESULT IN REJECTION OF YOUR OFFER. If by virtue of this amendment you desire to change an offer already submitted, such change may be made by telegram or letter, provided each telegram or letter makes reference to the solicitation and this amendment, and is received prior to the opening hour and date specified.

12. ACCOUNTING AND APPROPRIATION DATA (If required)

13. THIS ITEM APPLIES ONLY TO MODIFICATIONS OF CONTRACTS/ORDERS, IT MODIFIES THE CONTRACT/ORDER NO. AS DESCRIBED IN ITEM 14.

(✓)	A. THIS CHANGE ORDER IS ISSUED PURSUANT TO: (Specify authority) THE CHANGES SET FORTH IN ITEM 14 ARE MADE IN THE CONTRACT ORDER NO. IN ITEM 10A.
	B. THE ABOVE NUMBERED CONTRACT/ORDER IS MODIFIED TO REFLECT THE ADMINISTRATIVE CHANGES (such as changes in paying office, appropriation date, etc.) SET FORTH IN ITEM 14, PURSUANT TO THE AUTHORITY OF FAR 43.103(b).
	C. THIS SUPPLEMENTAL AGREEMENT IS ENTERED INTO PURSUANT TO AUTHORITY OF:
	D. OTHER (Specify type of modification and authority)

E. IMPORTANT: Contractor ☐ is not, ☐ is required to sign this document and return _____ copies to the issuing office.

14. DESCRIPTION OF AMENDMENT/MODIFICATION (Organized by UCF section headings, including solicitation/contract subject matter where feasible.)

Standard Form 1442 and Specifications for SOCIAL WORK SERVICES CLINIC, FORT HOOD, TEXAS, are amended as follows:

a. Standard Form 1442- Item 13.A.- In the second line, change the Bid Opening date from "13 January 1998" to "16 January 1998". Bid opening time will be 2 p.m. CST.

b. The following accompanying new section, bearing the notation "ACCOMPANYING AMENDMENT NO. 0002 TO SOLICITATION NO. DACA63-98-B-0002" shall be added to the specifications and add to the Table of Contents:

Section No. Title
10201 METAL WALL LOUVERS

Except as provided herein, all terms and conditions of the document referenced in Item 9A or 10A, as heretofore changed, remains unchanged and in full force and effect.

15A. NAME AND TITLE OF SIGNER (Type or print)		16A. NAME AND TITLE OF CONTRACTING OFFICER (Type or print)	
15B. CONTRACTOR/OFFEROR		16B. UNITED STATES OF AMERICA	
<div style="border-bottom: 1px solid black; width: 100%;"></div> (Signature of person authorized to sign)		BY <div style="border-bottom: 1px solid black; width: 100%;"></div> (Signature of Contracting Officer)	
15C. DATE SIGNED		16C. DATE SIGNED	

SECTION 10201

METAL WALL LOUVERS

PART

1 - GENERAL

1.1 REFERENCES

The publications listed below form a part of this specification to the extent referenced. The publications are referred to in the text by the basic designation only.

AIR MOVEMENT AND CONTROL ASSOCIATION, INC. (AMCA)

AMCA 500 (1991) Louvers, Dampers and Shutters

AMCA 511 (1986) Certified Ratings Program for Air Control Devices

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM A 653/A 653M (1995) Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process

ASTM B 209 (1995) Aluminum and Aluminum-Alloy Sheet and Plate

1.2 SUBMITTALS

Government approval is required for submittals with a "GA" designation; submittals having an "FIO" designation are for information only. The following shall be submitted in accordance with SECTION 01300 SUBMITTAL PROCEDURES:

SD-01 Data

Metal Wall Louvers; FIO

Provide manufacturer's standard catalog data.

SD-04, Drawings

Wall Louvers; GA

Show all information necessary for fabrication and installation of louvers. Indicate materials, sizes, thicknesses, fastenings, and profiles.

1.3 DELIVERY, STORAGE, AND PROTECTION

Deliver materials to the site in an undamaged condition. Carefully store materials off the ground to provide proper ventilation, drainage, and protection against dampness. Louvers shall be free from nicks, scratches, and blemishes. Replace defective or damaged materials with new.

ACCOMPANYING AMENDMENT NO. 0002 TO SOLICITATION NO. DACA63-97-B-0002

PART 2 PRODUCTS

2.1 MATERIALS

2.1.1 Galvanized Steel Sheet

ASTM A 653/A 653M, coating designation G90.

2.1.2 Aluminum Sheet

ASTM B 209, alloy 3003 or 5005 with temper as required for forming.

2.2 METAL WALL LOUVERS

Weather resistant type, with bird screens and made to withstand a wind load of not less than 40 pounds per square foot. Wall louvers shall bear the AMCA certified ratings program seal for air performance and water penetration in accordance with AMCA 500 and AMCA 511. The rating shall show a water penetration of 0.20 ounce or less per square foot of free area at a free velocity of 800 feet per minute.

2.2.1 Formed Metal Louvers

Formed of zinc-coated steel sheet not thinner than 16 U.S. gage, or aluminum sheet not less than 0.08 inch thick.

2.2.2 Mullions and Mullion Covers

Same material and finish as louvers. Provide mullions for all louvers over 5 feet in width. Provide mullion covers on both faces of joints between louvers.

2.2.3 Screens and Frames

For aluminum louvers, provide 1/2 or 1/4 inch square mesh, 16 gage aluminum bird screening. For steel louvers, provide 1/2 or 1/4 inch square mesh, 16 gage zinc-coated steel bird screening. Mount screens on the interior face of louver in removable, rewirable frames of same material and finish as the louvers.

2.3 FASTENERS AND ACCESSORIES

Provide stainless steel screws and fasteners for aluminum louvers and zinc-coated or stainless steel screws and fasteners for steel louvers. Provide other accessories as required for complete and proper installation.

2.4 FINISHES

Louvers and related trim shall be factory finished with a topcoat of 70% polyvinylidene fluoride resin with not less than 0.8 mils dry film thickness applied to a cleaned, pretreated and primed surface. The prime coat shall have not less than 0.2 mils dry film thickness. Color for louvers shall be as selected for standing seam metal roof system and sheet metalwork in Sections 07416 and 07600, respectively.

ACCOMPANYING AMENDMENT NO. 0002 TO SOLICITATION NO. DACA63-97-B-0002

PART 3 EXECUTION

3.1 INSTALLATION

3.1.1 Wall Louvers

Install using stops or moldings, flanges, strap anchors, or jamb fasteners as appropriate for the wall construction and in accordance with manufacturer's recommendations.

3.1.2 Screens and Frames

Attach frames to louvers with screws or bolts on the interior side of louver only.

3.2 PROTECTION FROM CONTACT OF DISSIMILAR MATERIALS

3.2.1 Aluminum

Where aluminum contacts metal other than zinc, paint the dissimilar metal with a primer and two coats of aluminum paint.

3.2.2 Metal

Paint metal in contact with mortar, concrete, or other masonry materials with alkali-resistant coatings such as heavy-bodied bituminous paint.

3.2.3 Wood

Paint wood or other absorptive materials that may become repeatedly wet and in contact with metal with a coat of heavy-bodied bituminous paint.

-- End of Section --